



Dimensions in inches (mm in parentheses).
Dimensions are for reference only.

Product List

Model Number	Description
7150	

Features & Benefits

- 8,600 Raw Lumens; 5,400 Effective Lumens
- Available in a 12-24V DC configuration
- Flood, Spot & Trapezoid beam patterns available
- UV-resistant polycarbonate lens
- Rugged solid state LEDs can withstand shock & vibration
- Long-lasting LEDs mean never having to replace another bulb again!
- Die-cast magnesium housing provides maximum protection
- Universal pedestal mount
- Fully sealed to withstand high-power washing & extreme industrial environmental conditions (**Complies with IP69K**)

General Specifications

Lens Pattern :	Flood, Spot or Trapezoid
Lens Material :	Polycarbonate
Housing Material :	Die-Cast Magnesium
Mounting Hardware:	(x1) 1/2" Mounting Bolt
Mounting :	Universal Pedestal Mount
Connector:	Integrated 2-Pin Deutsch Weather-Proof Socket (DT04-2P)
Mating Connector:	2-Pin Deutsch Weather-Proof Plug (DT06-2S)
Weight:	2.8 lbs

Technical Specifications

7150
12-24V DC Input
6.50 Amps @ 12V DC
3.50 Amps @ 24V DC
Raw Lumen Output: 8,600
Effective Lumen Output: 5,400

Standards Compliance

Buy America Compliant	SAE J575
SAE J1113	SAE J1455
Sealed to IP69K	

Applications

Construction	Forestry	Industrial
Mining	Off-Highway	Specialty Trucks
Utility		

Additional Info

Wires: Red=Positive, Black=Negative
Transient Spike Protection: 150V Peak @ 1 HZ-100 Pulses

Model 7150 XL

